












Myloc8 GPS Tracker


Myloc8 Tracker is our best-selling, versatile GPS tracker equipped with an SOS button, providing reliable location tracking and peace of mind for users in any situation.



Unique features

-  **Real-Time alerts**
Immediate location change alerts and multiple geofence setups.
-  **Two programmable buttons**
-  **Worldwide coverage**
-  **Durable**
-  **Speed monitoring**
-  **Ultra long battery life**
Up to 12 days per charge, depending on mode of operation and cellular network conditions.
-  **Strong magnet attachment**
-  **Geofencing**
-  **One account for all your devices**

Myloc8 application



SIM card included

Myloc8 is part of the Trackimo™ Group, a world-leading provider of personal safety and asset tracking IoT solutions, combining hardware, software, and communications expertise for over 15 years. We are trusted by global partners such as Vodafone™ and Paramount™.



Specifications

Cellular

Stock Code	MYLC003
Network technology	LTE(4G) CAT1
Frequency bands	TDD LTE: B40, B41(B38) FDD LTE: B1,B2,B3,B4,B7,B8, B26(B18/19/5), B20, B12(B17), B28
Data support	SMS, UDP / IP TCP / IP
SIM card	Embedded SIM or nano-SIM
Roaming data	Yes
Antena	Embedded cellular antenna

Positioning

GNSS receiver	22 tracking / 66 acquisition channels
GNSS engine	GPS, Galileo, Beidou, GLONASS, QZSS and SBAS
Other location technology	Wi-Fi Networks / Cell ID
SBAS support	WAAS, EGNOS, GAGAN, BDSBAS, MSAS
Tracking sensitivity	-160dBm tracking sensitivity -147dBm Acquisition sensitivity with cold start
Acquisition time	Hot Start < 2 seconds (open sky) Cold Start < 24 seconds (open sky)
Location accuracy	< 5 meters (open sky)
A-GPS	Supported

Wireless

Bluetooth	BLE v5.2
Wi - Fi	802.11b/g/n

Environmental

Operating temperature	-20°C to +60°C (recharge 0°C to +40°C)
Humidity	95%RH@ 50°C Non-condensing

Sensors

Accelerometer	3-axis ±16g
---------------	-------------

Electrical

Operating voltage	3.7 V
Battery type	Rechargeable Li-ion
Battery capability	600 mAh
Battery life	Up to 12 days, depending on mode of operation and cellular network conditions

Physical

Dimensions	47 mm x 40 mm x 17 mm
Weight	35 g

Connectors

USB charger	Micro USB 5 Volts 500 mA
-------------	--------------------------

Application features

Full data or alert only	Full data
Maps	✓
Real time updates	✓
Geo speed alerts	✓
Geo fence alerts	✓
Travel history available	Up to 365 days
Alerts	Email, SMS, Push
No of location samples	Unlimited
Customizable tracking	✓
Global tracking	✓
SOS alarm	✓
Minimal update interval	5 Sec*
Play sound	✓

Certifications

Standards	FCC/ISED/CE/ROHS/REACH/ JATE/TELEC
-----------	---------------------------------------

* The minimum standard tracking period is 60 seconds. Faster tracking costs might vary. Please contact your sales representative for more details.

Last updated: 26 June 2025